



FRANCESCA'S PAINTS LTD

FRANCESCA'S MATT EMULSION

A smooth matt emulsion, providing a top quality and wipeable finish for interior walls and ceilings.

TYPE OF SUBSTRATE

Plaster and embossed wallcoverings. Also suitable on wallboards, concrete, cement rendering, brickwork and blockwork in interior situations.

COVERAGE

1 litre will cover approximately 14 square meters depending on porosity of surface. Strong colours might require additional coats.

DRYING TIME

Touch dry 1-2 hours. Allow 6-8 hours before applying the second coat. **Dark colours will need 24 hours before applying the second coat.** Paint has to harden well before receiving the second coat

PREPARATION

Ensure surface is sound, clean, dry and free from grease. Remove all loose and defective paint. Rub down glossy surfaces with fine waterproof abrasive paper. Seal absorbent surfaces with a solution of up to 1 part of water to 9 part of Matt Emulsion.

APPLICATION

Stir well before use. Do not thin, except for absorbent surfaces, or when applying by roller or spray when a small quantity of clean water may be added. **Suitable for application by brush, roller or spray.** Apply evenly and avoid overspreading. Apply second coat after 2-4 hours. Do not apply in temperature below 10C.

CLEANING

Remove as much product as possible from application equipment immediately after use in soapy water and rinse thoroughly. Do not empty product into drains or watercourse. Replace lid firmly.

GENERAL INFORMATION

Colour variation can occur between batches due to the natural pigments used, therefore, it is recommended that all Francesca's Vinyl Matt be purchased at the same time. Keep the lid tightly on. Keep out of reach of children. Do not swallow and avoid eye contact. If accidental contact occurs, rinse eyes with copious amounts of water. WHEN USING MORE THAN ONE TIN COLOUR IN THE SAME ROOM, INTERMIX BEFORE USE

WARRANTY AND LIABILITY DISCLAIMER

The information supplied herein is offered in good faith. There are no implied conditions of warranty. The manufacturer's guarantee is limited to product replacement only and does not include surface preparation and application.